



# 'Light' proving tanks

## 5-10-20 liters

Data sheet: DS/MC/0001/EN Ed. 02-2021

'Light' model proving tanks are used for calibration of p.d. meters, as well as dosing pumps, tanks and fuel dispensers.

### Standards

These proving tanks conform to OIML R120 International Recommendation.

Tolerance of measurement is as follows:

5 L	→	± 5 mL	} Compliant also with OIML R120
10 L	→	± 5 mL	
20 L	→	± 10 mL	

### Gauge scale / range


5 L	→	5 mL / ± 30 mL
10 L	→	5 mL / ± 50 mL
20 L	→	10 mL / ± 200 mL

Upon request: the proving tank can be supplied with calibration certificate recognized by EA (for Europe) and ILAC-MRA (International Certificate).

Wooden case available upon request.

### Technical features

CAPACITY	DIMENSIONS (mm)			WEIGHT (KG)
	A	B	C	
5 LITERS	210	48	380	2,5
10 LITERS	210	48	490	3,5
20 LITERS	262	67	695	6,3



### Construction

Body:	AISI 304
Reading scale:	Plexiglass, on the neck of the proving tank
Gauge plate:	AISI 304, adjustable for calibration and fixed on the neck with sealed screws
Cap:	Rubber

www.isoilmeter.com